



C-Strobe™

Product No. 3958 Bulk/3959 Carded Life preserver emergency signaling strobe

- > Intense strobe light visible up to 2 miles (3.2 km)
- > Waterproof and corrosion resistant case
- > New attachment pin engages top cap; prevents accidental disassembly
- > Slim, lightweight design
- > Comes with steel clip and adjustable Velcro strap; can be mounted on bicycle frame or pole, etc.
- > Operates on 2 "AA" alkaline or 2 "AA" 1.5V lithium batteries (5-year replacement life when using lithium batteries; 1-year replacement life when using alkaline batteries)
- > Operating life—More than 8 hours continuous @ -1°C (30°F)

Size: 6.0 x 1.6 in (15.3 x 4.0 cm)

Weight: 2.6 oz (74 g)

Material: Rugged, impact and temperature resistant ABS

Color: International orange

Operation: Twist "ON-OFF" control can be operated by gloved hands and in adverse conditions

Waterproof: Up to 10 ft (3.1 m)

Accessories: 1083—Dated lithium batteries;
9433—C-Clip Rescue Light Adapter for Inflatable PFDs

Beam Angle: Omni-directional 360°

Visibility: High intensity strobe light is visible up to 2 miles (3.2 km)

Flash Rate: 60 ±10 flashes per minute nominal

Lamp: Xenon flash tube

Battery Type: 2 "AA" alkaline or 1.5V lithium (not included);
release pin before battery replacement

Certification: USCG 161.012/41/0 approved with 2 "AA" lithium; CE

Limited Warranty: 1 year

Carton Dimensions: 3958—7.0 x 12.0 x 5.0 in (18.0 x 30.0 x 13.0 cm)
3959—13.5 x 13.5 x 9.0 in (34.0 x 34.0 x 23.0 cm)

Units Per Carton: 3958—24
3959—12

Carton Weight: 3958—4.8 lbs (2.2 kg)
3959—4.5 lbs (2.0 kg)

Operational Life: More than 8 hours continuous @ -1°C (30°F)



ACR Electronics, Inc.

5757 Ravenswood Road
Fort Lauderdale, FL 33312, U.S.A.
Tel Worldwide: +1(954) 981-3333
Fax: +1(954) 983-5087
www.acrelectronics.com