

Firefly[®] 2 / Waterbug[™] / Doublefly[™]

Product No. 3900.1 Carded/3995 Bulk
Rescue strobe light

Product No. 3906.1 Carded/3996 Bulk
Water activated rescue strobe light

Product No. 3999.1 Carded/3999 Bulk
Rescue Combo Light, Strobe/Incandescent

- > 3900.1/3995—Manually activated rescue strobe
- > 3996.1/ 3996—Special water activation feature automatically activates light should wearer fall into water
- > 3999.1/3999—Multi-function switch selects between strobe light for visibility at great distances or steady incandescent light for close-up recovery work
- > 360° high intensity Xenon strobe visible for many miles
- > Large sliding switch allows for easy operation by gloved hands
- > Base platform allows unit to stand upright easily
- > Conceived as state-of-the-art replacement for famous Firefly[®] forerunners, 4F and 4G
- > Designed as "electronic flare" to replace day/night pyrotechnic signal in aviation life rafts
- > Stainless steel retainer securely attaches removable battery door to case
- > Integral lashing loops provide a secure anchor point
- > Uses 2 "AA" alkaline or 2 "AA" 1.5V lithium batteries for extended useful life
- > Operating life—Strobe: minimum 8 hours continuous to meet USCG specifications; Incandescent: 2 hours continuous

Battery Size: 4.4 x 2.2 x 1.1 in (11.0 x 5.6 x 2.5 cm)

Weight: 4.0 oz (113 g)

Material: Polycarbonate

Color: International orange

Operation: 3900.1/3995—slide switch up to "ON" position; 3996.1/3996—lights when in water with switch "ON"; 3999.1/3999—Multi function switch "ON - OFF - ON"

Waterproof: Up to 200 ft (61 m)

Beam Angle: Omni-directional 360°

Accessories: A6-04-0087—Orange pouch with lanyard

Visibility: Visible up to 3 mi (5 km)

Flash Rate: 60± 10/minute, nominal

Lamp: High intensity Xenon strobe; Incandescent

Battery Type: 2 "AA" alkaline or 1.5V lithium (not included)

Certification: 3900.1/3995/3996.1/3996—USCG 161.012/29/0 approved; FAA (TSO-C85) approved CE; 3999.1/3999—CE

Limited Warranty: 1 year

Carton Dimensions: Carded—6.5 x 5.0 x 11.0 in (16.5 x 12.7 x 28 cm)

Units Per Carton: Carded—6

Carton Weight: Carded—1.9 lbs (.9 kg)

Operational Life: Strobe: minimum 8 hours continuous to meet USCG specifications; Incandescent: 2 hour continuous



ACR Electronics, Inc.

5757 Ravenswood Road
Fort Lauderdale, FL 33312, U.S.A.
Tel Worldwide: +1(954) 981-3333
Fax: +1(954) 983-5087
www.acrelectronics.com

A Chelton Group Company