

RCL - 50B



RCL-50B

Product No.1939.3 (12V)

RCL-100D

Product No. 1930.3 (12V)

1931.3 (24V)

Remote Controlled Searchlight

- > RCL-50B - 80,000 candela
- > RCL-100D - 200,000 candela
- > Internal elevation mechanism provides pitch control of spotlight beam while protecting elevation mechanism from weather
- > High intensity 55W Halogen lamps and parabolic reflectors provide intense concentrated spotlight beam
- > Salt water-resistant construction with nylon and phenolic washers, aluminized stainless steel screws with insulating lubricant
- > Housing rotates a full 360° allowing all-around illumination capability
- > RCL-100D - Option of 12 or 24VDC operating system
- > Includes a fingertip remote control Point Pad™; up to three remote Point Pad™ units may be installed on system
- > Rugged triple-primed and sealed, marine grade aluminum housing
- > Application: Sport yachts, mega-yachts, sport fish and commercial vessels
- > Both lights shipped with new URP-102 Point Pad, and new URC-102 master controller. URC-102 master controller now with XRCIZ® feature. XRCIZ® feature rotates and moves light assembly every 30 days from activation to keep the search lights motors and drive mechanism freely running

Size: RCL-50B-8.4 x 6.0 x 8.0 in
(21.3 x 15.2 x 20.3 cm)

RCL-100D-8.0 x 9.0 x 8.0 in
(20.3 x 22.9 x 20.3 cm)

Weight: RCL-50B - 6.2 lbs (2.8 kg)
RCL-100D - 7.2 lbs (3.2 kg)

RCL - 100D



- Material:** Aluminum; RCL-100D 518 Aluminum
- Color:** White
- Operation:** Remote controlled
- Accessories:** 9282.3 - Secondary Point Pad™ for remote control with install kit
Replacement Halogen Lamps:
6002 - RCL-50B - 55W/12V
6001 - RCL-100D - 55W/12V
6003 - RCL-100D - 55W/24V
1925 - 12V searchlight only
1926 - 24V searchlight only
- Beam Angle:** RCL-50B - 7°
RCL-100D - 5° vertical, 7° horizontal
- Elevation Angle:** RCL-50B - 20° up, 20° down
RCL-100D - 10° up, 17° down
- Rotation:** 360°
- Rotation Speed:** RCL-50B - 15° per second
RCL-100D - Fast 28° per second, slow 15° per second
- Elevation Speed:** RCL-50B - 6° per second
RCL-100D - 2°-7° per second (12VDC)
RCL-100D - 5°-8° per second (24VDC)
- Lamp:** High intensity 55W Halogen
- Limited Warranty:** 1 Year
- Carton Dimensions:** RCL-50B 12.5x8.0x11.5 in
(32.0x20.0x29.0 cm)
RCL-100D 13.0x21.0x10.0 in
(33.0x53.0x25.4 cm)
- Carton Weight:** RCL-50B 9.0 lbs (4.0 kg)
RCL-100D 14.0 lbs (6.3 kg)
- Units Per Carton:** 1



ACR Electronics, Inc.

5757 Ravenswood Road
Fort Lauderdale, FL 33312, U.S.A.
Tel Worldwide: +1(954) 981-3333
Fax: +1(954) 983-5087
www.acrelectronics.com