

Specifications Sheet



Motorola Canopy

5.4 GHz Backhaul, 20 Mb



Description	5.4 GHz Backhaul, 20 Mb
Canopy Part Number	5400BH20
Market Availability	not currently available in the US
Signaling Rate	20 Mbps
Typical LOS Range	1 mi (1.6 km)
Typical Aggregate Useful Throughput	14.0 Mbps
Frequency range of band	U-NII 5470-5725 MHz
Non-overlapping Channels	3
Channel Width	20 MHz
Channel Spacing	every 5 MHz
Modulation Type	High Index 4-level Frequency Shift Keying (FSK) optimized for interference rejection
Encryption	DES capable
Latency	2.5 msec
Carrier to Interference ratio (C/I)	-3dB @ 10 Mbps, -10dB @ 20 Mbps at -65dBm
Nominal Receiver Sensitivity (dbm typical)	-79 dB
Antenna Gain (dB)	7 dB
EIRP (dB)	30 dB
Equivalent Isotropic Radiated Power (EIRP)	1W
DC Power (typical)	0.34 A @ 24 VDC = 8.2 W
Antenna Beam Width	3 dB antenna beam width 60 degrees, Azimuth and Elevation
Mean Time Between Failure (MTBF)	40 yr
Temperature	-40° C to +55° C (-40° F to +131° F)
Wind Survival	190 km/hr (118 miles/hr)
Dimensions	11.75 in H x 3.4 in W x 3.4 in D (29.9 cm H x 8.6 cm W x 8.6 cm D)
Weight	.45 kg (1 lb)
Access Method	Time Division Duplex (TDD)
Interface	10/100 Base T, half/full duplex. Rate auto negotiated (802.3 compliant)
Protocols Used	IPV4, UDP, TCP, ICMP, Telnet, HTTP, FTP, SNMP Version 2C
Network Management	HTTP, TELNET, FTP, SNMP Version 2c
CE	"CE" marked & compliant to EN301 893, Implements DFS & TPC. DoCs are available at http://www.canopywireless.com/doc.php

Specifications subject to change without notice.