

## Specifications Sheet



### Motorola Canopy 5.7 GHz Advantage Access Point Module



Description	5.7 GHz Advantage Access Point Module
Canopy Part Number	5750AP
Market Availability	North America, Europe, South America, Asia
Signaling Rate	10 Mbps
Typical LOS Range	2 mi (3.2 km)
Typical Aggregate Useful Throughput	7.0 Mbps
Frequency range of band	ISM 5725-5850 MHz
Non-overlapping Channels	6
Channel Width	20 MHz
Channel Spacing	every 5 MHz
Modulation Type	High Index 2-level Frequency Shift Keying (FSK) optimized for interference rejection
Encryption	DES capable
Latency	5 - 7 msec
Carrier to Interference ratio (C/I)	<3 dB
Nominal Receiver Sensitivity (dbm typical)	-86
Antenna Gain (dB)	7
EIRP (dB)	30
Equivalent Isotropic Radiated Power (EIRP)	1 W
DC Power (typical)	0.3 A @ 24 VDC = 7.2 W
Antenna Beam Width	3 dB antenna beam width 60 degrees, Azimuth and Elevation
Temperature	-40° C to +55° C (-40° F to +131° F)
Wind Survival	190 km/hr (118 miles/hr)
Dimensions	11.75 in H x 3.4 in W x 3.4 in D (29.9 cm H x 8.6 cm W x 8.6 cm D)
Weight	.45 kg (1 lb)
Access Method	Time Division Duplexing/Time Division Multiple Access (TDD/TDMA)
Interface	10/100 Base T, half/full duplex. Rate auto negotiated (802.3 compliant)
Protocols Used	IPV4, UDP, TCP, ICMP, Telnet, HTTP, FTP, SNMP
Network Management	HTTP, TELNET, FTP, SNMP Version 2c
FCC ID	ABZ89FC5804
Industry Canada Certification Number	109W-5700
NYCE	0202CE08128

Specifications subject to change without notice.

MOTOROLA and the Stylized M Logo are registered in the U.S. Patent and Trademark Office. All other product or service names are the property of their respective owners. © Motorola, Inc. 2005