





Motorola ML910 Mid Tier Docking Station

| Antenna Pass-Through | Weight | Height | Width | Depth |
|----------------------|----------|--------|-------|--------|
| NA | 13.5 lbs | 5.0" | 12.0" | 11.75″ |

Features

- Designed using MIL-STD-810F test procedures
- Internal /protected circuit board and power supply protect against dirt and dust
- Simple latching action:
 - Pull front handle to insert the docking connector and secure the latching brackets
 - Push front handle to release the latches and disengage the docking connector
- Locating pins for assured computer placement
- Floating docking connector for reliable docking connection
- Recessed backward facing ports allow for dock to be mounted up to the dash
- Loops and slots provided for strain relief of all cables
- Rounded edges to enhance personal safety
- 1 year limited warranty (printed circuit board and docking connector)
- 3 year limited warranty (on all sheet metal components)
- Heavy gauge steel construction for long-term durability
- Black powdercoat finish for maximum corrosion resistance

Port Replicator

- Serial (2) D-sub 9 pin - Parallel (1) - USB (2) 4 pin - External video D-sub 15 pin - Output Amp: 4.74A

- Ethernet RJ45

- Auxiliary

- BNC Composite Video

Integrated Speaker Yes

Internal Power Supply

- Operating Temperature: 0° C to 50° C (32° F to 122° F)

D-sub 25 pin - Input Voltage: 11V DC - 16V DC

- Output Voltage: 19V DC

- Over Voltage Protection: 16Vdc - 27Vdc

- Under Voltage Protection: 11Vdc

- LED Power Indicator Light: Green LED

- Docked Indicator Light: Amber LED

Reverse Voltage Protection

- Input fused

- Output current limit

Item No. 7170-0004





3001 Borham Ave Stevens Point, WI 54481 Phone: 800-456-6868 Fax: 715-344-8845

Email: gamberj@gamberjohnson.com Website: www.gamberjohnson.com

