

SEA 245

150 Watt MF/HF/SSB Digital Radiotelephone



- The SEA245 is a highly integrated and compact solid state MF/HF SSB Radiotelephone transceiver with internal DSC Controller. The SEA 245 is Type Certified for Sea Area A2 GMDSS stations and is also suitable in any general purpose MF/HF radiotelephone application.
- Internal DSC Controller, MF Watch Receiver for A2 and optional SEATOR modem
- A 245 model for Sea Area A3 GMDSS is also available
- RF transmit power in SEA 245 SSB radios can be programmed
- The SEA245 SSB radiotelephone utilizes Digital Signal Processing (DSP) technology as its fundamental architecture.
- DSP end-user benefits include:
 - Digital transmitter provides more talk power than radiotelephones with equal power ratings
 - Superior gain control (AGC) provides virtually error free transition between voice and data
 - Clean clear audio with enhanced clarity and reception
 - Installed SEA 245s will receive future enhancements and improvements through software upgrades
 - Uniquely flexible with special application filters (sitor, telex, modems) software configurable
 - Increased reliability over pure analog radios
- Amateur bands with comprehensive HAM band operating system built-in
- RS-232 Serial PC interface supports radio control applications and E-mail service providers
- Most frequently used channels are pre-programmed from factory using alpha-numeric names for easy recall
- True AM receiver for clear undistorted reception of AM frequencies
- Large easy to read Graphic Display
- Backlighted silicone keypad
- GMDSS compatible
- NMEA 0183 position input
- Model 3000G SITOR Modem available
- Optional Remote Display/Control Terminal available

The SEA245 SSB/DSC radiotelephone is designed and constructed on a fully digital platform. This revolutionary radio is unequalled in performance, price, reliability, and flexibility for use in numerous special applications.

SEA Inc. is the company that provided the marine marketplace with an economically-priced synthesized SSB radiotelephone over 20 years ago.

SEA SSB radiotelephones have consistently won National Marine Electronics Association's (NMEA) awards for excellence in SSB radiotelephone design.

245 Specifications

Dimensions in. (mm)

GENERAL:

Compliance:

FCC Parts 80, 87, 90
CEPT pending application,
ITU R M.493, ITU R M.541,
IMO A.804, IMO A.806

FCC ID:

BZ6SEA245

Frequency Range:

Tx: 1.6 to 29.999 MHz
Rx: .49 to 29.999 MHz

Frequency Stability:

±10 Hz (-30°C to +60°C)

Operating Modes:

J3E (USB), H3E, R3E,
J2B (AFSK), A1A (CW)
F1B (TELEX)

Supply Voltages:

24 Vdc -10% +25%
(21.6 to 30 V)

Current Drain:

Tx: 8 Amps (two-tone)
Tx: 6 Amps (voice)
Rx: 1 Amp (stand-by)
Rx: 1.5 Amps (full-audio)

Operating Temperature

Range:

-30°C to 60°C

Antenna Impedance:

50 ohms

Channels:

1176 Total
200 Programmable
242 ITU SSB Duplex
72 IUT SSB Simplex
662 ITU FSK Duplex

Scan Channels:

200

Display:

Graphic Display
3.2" x 1.85" (W x H)
(81.2mm x 46.9mm)

Metering:

S-Meter

Computer I/O:

RS-232

RECEIVER:

Frequency Range:

490 KHz to 29.999 MHz

Frequency Resolution:

10 Hz

Intermediate

Frequencies:

1st 45 MHz, 2nd 40 KHz
(nominal) DSP

Sensitivity:

≤ 1.0 uV for 12 dB SINAD

Adjacent Channel

Selectivity:

>55 dB at -1 KHz

Blocking:

At max. sensitivity: Better
than 70dB. At +60dB/uV:
Better than 100 dB

Cross Modulation:

Better than 80 dB

Spurious Response:

Better than 70 dB

Spurious Emissions:

Less than 1 nW

Intermodulation:

-80 dB

AGC:

J3E, fast attack, slow
release, ≤ 10 dB audio level
change from 10 uV to
100 mV input

Clarifier:

+/-200 Hz in 10 Hz steps

Squelch:

Voice controlled, opens at
SINAD >5dB

Audio Output:

4 Watt into 4 ohms at less
than 10% distortion

TRANSMITTER:

Output Power:

R3E, J3E 150 Watts PEP
F1B 100 Watts

Power Reduction:

-3dB/-6dB from PEP

Intermodulation:

Better than -34 dB
below PEP

Spurious Emissions:

Better than -65 dB
below PEP

Carrier Suppression:

Better than 46 dB below
PEP



Undesired Sideband

Suppression:

Better than 41 dB below
PEP

AF Bandwidth:

400 to 2500 Hz at -6 dB



Radio
9.1 lbs (4 kg.)



American technology that talks to the world.

7030 - 220th S.W., Mountlake Terrace, Washington 98043; (425) 771-2182; Fax: (425) 771-2650; www.sea-dmi.com