

NEW!

Sea Tel 4010 and 5010

3-Axis Maritime Stabilized Antenna for Always-On Ku networks for the bandwidth conscious customers

2010 Data Sheet

The most important thing we build is trust



4010 and 5010 Ku-Band Antennas

The XX10 is in the long line of how-did-we-ever-live-without-this technology products from Sea Tel. It is designed for maritime applications and is expected to be available in 1m and 1.2m antennas.

The XX10 platform antenna will be offered with several customizable options. The Co Pol option, for instance, allows the customers global Ku coverage on co pol and cross pol services.

The XX10 platform antenna is also offered with extremely low loss waveguide in the transmit signal path option to operate with co pol services. The 5010 is optimized to increase customer ROI. When used in a 1m network, customers can have almost 40% more bandwidth and sail further out on the fringes of the foot print.

By upgrading the network to 1.2m, service providers can increase profit even further by adding about 40% more customers for the same space segment cost.

Product Benefits:

- Optimized to increase ROI for service providers.
- Generate higher ROI by replacing 4009 with 5010 antenna.
- Expand the foot print even further out.
- Sturdy construction outperforms competition.
- Enables regional or global communications with any service.
- Industry leading Stabilization Accuracy connected to the Always-On Network.
- Faster response to ship's motion.
- Very low loss waveguide rotary joint assembly ensures highest signal integrity.
- Reduces cost of support with latest remote software.

Product Features:

- 5010 has higher RF performance than 4009.
- Designed to meet EN 60945, MIL STD 461, MIL STD 167-1, and IEC 60950 specifications. Available in Co Pol or X-Pol configuration.
- Lighter weight and easier to install.
- Stabilized to isolate the antenna from the ship's motion.
- New software features and electronics integrates with Uplogix for automated response management.
- Available in C (coaxial) and W (waveguide) versions.
- 4010 is available in 50" and 60" radome.
- 5010 is available in 66" radome.



Sea Tel's 3-axis stabilization system isolates the antenna from the ship's motion no matter how rough the weather and seas. The antenna system responds to ship's movement at a rate as fast as 90 degrees per second.

Sea Tel 4010 and 5010




Selection Guide

Model	Antenna Size	Rx*	Tx*	G/T*	BUC	EL	Crosslevel	AZ	Apprx. Weight
		dBi @ 12.5 GHz	dBi @ 14.25 GHz	@ 30 Deg. Clear Sky, dB/K	(watts)	in Degrees at 20° Roll	in Degrees		Lbs/Kgs
4010	1m	39.10	39.90	17.10	8+	+5 to +90	±35 Deg	Unlimited	250/116
5010	1.2m	40.90	42.10	20.00	8+	+5 to +90	±35 Deg	Unlimited	325/148

Model	Wind	Rain	Temp	Roll	Pitch	Yaw	Turning Rate and Acceleration	Stability Accuracy
	Mph/Kmph			Deg @ 8 Sec Period	Deg @ 6 Sec Period	Deg @ 15 Sec Period		
4010	125/201	4"/hr	-20 TO 55 °C	24	14	8	UP TO 12 DEG/SEC AND 15 DEG/SEC ²	0.1 rms
5010	125/201	4"/hr	-20 TO 55 °C	24	14	8	UP TO 12 DEG/SEC AND 15 DEG/SEC ²	0.1 rms

*Gains reported are worst case, on-satellite gains should be higher. The C version antenna has less than 1.5 dB Tx path loss over the W version.



DAC 2202 Controller

- Model: 2202
- Mounting: Rack Mount
- M & C Ports: 1 Serial, 3 TCP/IP, 1 multi-user web browser support
- UDP Upload port for updating software in the Comm Interface
- Reformatted GPS output: (GGA and GLL)
- Heading Input: NMEA 0183, SBS, Synchro or No-Gyro Mode
- Dimensions: 19" X 1.75"



For further information please contact:

Cobham SATCOM Marine Systems

U.S.A. Tel: +1 925-798-7979
 Fax: +1 925-288-1420
 Toll Free: +1-888-798-7979
 E-mail: satcom.concordsales@cobham.com

EUROPE Tel: +44 2380 671155
 Fax: +44 2380 671166
 E-mail: satcom.southamptoneurosales@cobham.com

ASIA Tel: +65 6795-2205
 Fax: +65 6515 6546
 E-mail: daren.wong@cobham.com