

# EVX-S24

## DIGITAL PORTABLE RADIOS

DMR Tier 2 Standard /TDMA Protocol

**Vertex Standard**

eVerge™

SPECIFICATION SHEET - NORTH AMERICA

## Evolve to Better Communication and Value with our Smallest, Water Submersible Digital Portable Radio

You can afford to enhance your communications with the digital performance of eVerge™ two-way radios. eVerge™ radios are compact and precision-engineered to deliver value without sacrificing quality — giving you more capabilities and the flexibility you need to communicate at your best.

### Compact and Discreet

The EVX-S24 is our smallest and lightest digital radio. It is slim and easy to carry so it is ideal for hospitality, education, retail and for any market that values convenience and size.

### Water Submersible and Dust Proof

The EVX-S24 meets international standard IP67 for water submersibility and is dust proof. The EVX-S24 is protected from immersion in water up to 3 feet [1 meter] for 30 minutes and offers complete protection from dust.

### Conversion Made Easy with Digital to Analog Integration

eVerge™ radios operate in both analog and digital modes and can be used with any existing analog two-way radios.

### Direct Mode

Direct Mode enables you to have two communication paths on a single frequency effectively doubling your call capacity without the need of a repeater.

### Transmit Interrupt

When seconds matter, transmit interrupt allows an operator to halt or “interrupt” any current transmission, in favor of a priority message. Transmit Interrupt functionality ensures your critical messages will connect.

### Better Radio Call Quality

Digital eliminates noise and static from voice transmit to only deliver the intended voice message crisply and clearly. eVerge™ digital radios feature the AMBE+2™ vocoder for enhanced voice quality.

### Better Message Control and Privacy

Control who you call and who gets your message in digital mode. Digital radios each have a unique ID enabling users to select who they need to call or send a text message without including others.

### Site Search

Move between multiple sites seamlessly by using the Site Search functionality on your EVX-S24 radio. Manually or automatically initiate Site Search to identify the signal of the closest site with the strongest signal strength. The EVX-S24 portable will dynamically change its pre-programmed home site to the site with the strongest signal in range. Great for operations with multiple locations or buildings with multiple floors.



EVX-S24



IP67  
Water Submersible  
Dust Proof



## SPECIFICATION SHEET – NORTH AMERICA

### Additional Features

- ▶ Battery Status Indicator (Low Battery Alert)
- ▶ Battery Saver
- ▶ BCLO
- ▶ Time Out Timer
- ▶ Key Lock
- ▶ AF Minimum Volume
- ▶ Lone Worker Alert
- ▶ Emergency Alert
- ▶ Auto Power Off
- ▶ Escalating Alerts
- ▶ Low Power
- ▶ Whisper Mode
- ▶ Multiple Scan Options
- ▶ RSSI Indicator
- ▶ Internal VOX (VH-190 required)

### Signaling Features

- ▶ CTCSS/DCS Encode/Decode
- ▶ 2-Tone, 5-Tone
- ▶ DTMF Encode/Decode
- ▶ DTMF ANI
- ▶ DTMF Paging
- ▶ DTMF Speed Dial
- ▶ Stun/Kill/Revive (5 Tone and DTMF pager)
- ▶ MDC-1200® Features:
  - MDC-1200® ANI
  - MDC-1200® Call Alert
  - MDC-1200® Sel Call
  - MDC-1200® Radio Check
  - MDC-1200® Stun/Revive
- ▶ FleetSync® ANI (Encode Only)

### Analog Mode Features

- ▶ BTLO
- ▶ Auto Range Transponding System (ARTS™)
- ▶ Voice Inversion Encryption

### Digital Mode Features

- ▶ All, Group and Private Call
- ▶ Basic and Enhanced Privacy
- ▶ Radio Check
- ▶ Radio STUN/REVIVE
- ▶ Remote Monitor (Decode)
- ▶ CALL Alert
- ▶ Text Message
- ▶ Call History
- ▶ Simplex Only and Repeater Capable Encryption
- ▶ Direct Mode
- ▶ Emergency
- ▶ Radio Enable / Disable
- ▶ Scan (Mixed Mode - Analog/Digital Channels)
- ▶ Transmit Interrupt
- ▶ Scan (Operator Selectable On/Off)
- ▶ Site Search

### Accessories

- Antennas**
  - ▶ ATU-6A: 400-430 MHz 6.5" [16.51 cm]
  - ▶ ATU-6B: 420-450 MHz 6.1" [15.49 cm]
  - ▶ ATU-6C: 440-470 MHz 6.1" [15.49 cm]
  - ▶ ATU-6D: 450-485 MHz 6" [15.24 cm]
  - ▶ ATU-20AS: 400-430 MHz 3.15" [8 cm]
  - ▶ ATU-20CS: 420-450 MHz 3.15" [8 cm]
  - ▶ ATU-20DS: 440-470 MHz 3.15" [8 cm]
  - ▶ ATU-20FS: 450-480 MHz 3.15" [8 cm]
  - ▶ Super Stubby Antenna Selection\*
- ▶ Clip-27: Belt Clip
- ▶ Neck Lanyard\*
- Chargers**
  - ▶ PA-57B: Micro USB AC Charger [US]
  - ▶ PA-57C: Micro USB AC Charger [EU]
  - ▶ CD-65: Standard Single Unit Charging Cradle
  - ▶ CD-66: Enhanced Single Unit Charging Cradle\*
  - ▶ Multi Unit Charger\*
- Audio Accessories**
  - ▶ MH-89A4B: Earpiece Microphone
  - ▶ MH-90A4B: Compact Speaker Microphone\*
  - ▶ MH-66F4B: IP57 Submersible Speaker Microphone\*
  - ▶ VH-190: VOX Lightweight Headset, BTH\*

- Battery**
  - ▶ FNB-V142LI: 2300 mAh Li-Ion Battery

- Carry Solutions**
  - ▶ LCC-S24: Leather Case, Belt Loop\*
  - ▶ LCC-S24S: Leather Case, Swivel Belt Loop\*
- Programming Equipment**
  - ▶ CB000262A01: Programming Cable
  - ▶ CE157: PC Programming Software

**Specifications are preliminary and subject to change without notice or obligation.**

\* Coming soon.

VERTEX STANDARD is a trademark of Vertex Standard LMR, Inc. All other trademarks are the property of their respective owners. © Vertex Standard LMR, Inc. 2016 NSS\_S24\_09/2016

### EVX-S24 Specifications

General Specifications	
<b>Frequency Range</b>	UHF: 403 – 470 MHz
<b>Dimension [H x W x D]</b>	3.58 x 2.17 x 1.24 inches [91 x 55 x 31.5 mm]
<b>Weight Approx. with Antenna, Belt Clip</b>	7.6 oz [215 g] with [FNB-V142LI, ATU-20, Belt Clip]
<b>Display</b>	8 character alphanumeric
<b>Channel Spacing</b>	25' / 12.5 kHz
<b>Number of Channels and Groups</b>	256 / 16
<b>Programmable Buttons</b>	4 [Front: 3, Side: 1]
<b>Battery Life [5-5-90 duty with battery saver]</b>	Digital 3W: 12 hours / Analog 2W: 11 hours
<b>IP Rating</b>	67
<b>Power Supply Voltage</b>	3.7 VDC [nominal]
<b>Operating Temperature Range</b>	-22° F to +140° F [-30° C to +60° C]
<b>Frequency Stability</b>	± 1.5 ppm
<b>RF Input-Output Impedance</b>	50 Ohms
Receiver Specifications <small>measured by TIA/EIA 603</small>	
<b>Sensitivity</b>	Analog 12 dB SINAD: 0.25 uV Digital 1 % BER: 0.28 uV
<b>Adjacent Channel Selectivity</b>	TIA603: 70/60 dB [25 kHz / 12.5 kHz] TIA603D: 70/45 dB [25 kHz / 12.5 kHz]
<b>Intermodulation</b>	70 dB
<b>Spurious Rejection</b>	70 dB
<b>Audio Output</b>	500 mW @ 4 Ohms 10 % THD
<b>FM Hum and Noise</b>	45 / 40 dB [25 kHz / 12.5 kHz]
<b>Conducted Spurious Emission</b>	-57 dBm
Transmitter Specifications <small>measured by TIA/EIA 603</small>	
<b>Output Power</b>	Digital 3 W/2 W/1 W/0.5 W, Analog 2 W/1 W/0.5 W
<b>Modulation Limiting</b>	± 5 kHz [25 kHz]; ± 2.5 kHz [12.5 kHz]
<b>Conducted Spurious Emission</b>	-36 dBm [≤1 GHz], -30 dBm [≥1 GHz]
<b>FM Hum and Noise</b>	45 / 40 dB [25 kHz / 12.5 kHz]
<b>Audio Distortion</b>	< 5 % @ 1 kHz
<b>Adjacent Channel Power</b>	70 / 60 dB
<b>Analog FM Modulation</b>	16K0F3E [25 kHz], 11K0F3E [12.5 kHz]
<b>4FSK Digital Modulation</b>	12.5 kHz Data: 7K60F1D/7K60FXD 12.5 kHz Voice: 7K60F1E/7K60FXE Combination of 12.5 kHz Voice and Data: 7K60F1W
<b>Digital Vocoder Type</b>	AMBE+2
<b>Digital Protocol</b>	ETSI102 361-1, -2, -3

† 25 kHz not available for USA

### Applicable MIL-STD

Standard	Methods/Procedures				
	MIL 810C	MIL 810D	MIL 810E	MIL 810F	MIL 810G
<b>Low Pressure</b>	500.1 proc 1	500.2 proc 2	500.3 proc 2	500.4 proc 1/2	500.5 proc 1/2
<b>High Temperature</b>	501.1 proc 1/2	501.2 proc 1/A1 proc 2/A1	501.3 proc 1/A1 proc 2/A1	501.4 proc 1/HOT proc 2/HOT	501.5 proc 1/A1 proc 2/A2
<b>Low Temperature</b>	502.1 proc 1	502.2 proc 1/Cat 3 proc 2/Cat 1	502.3 proc 1/Cat 3 proc 2/Cat 1	502.4 proc 1/Cat 3 proc 2/Cat 1	502.5 proc 1/Cat 3 proc 2/Cat 1 proc 3/Cat 1
<b>Temperature Shock</b>	503.1 proc 1	503.2 proc 1/A1 Cat 3	503.3 proc 1/A1 Cat 3	503.4 proc 1	503.5 proc 1/C
<b>Solar Radiation</b>	505.1 proc 2	505.2 proc 1	505.3 proc 1	505.4 proc 1	505.5 proc 1/A1
<b>Rain</b>	506.1 proc 1/2	506.2 proc 1/2	506.3 proc 1/2	506.4 proc 1/3	506.5 proc 1/3
<b>Humidity</b>	507.1 proc 2	507.2 proc 2	507.3 proc 2	507.4	507.5 proc 2/Agg
<b>Salt Spray/Fog</b>	509.1 proc 1	509.2 proc 1	509.3 proc 1	509.4	509.5
<b>Dust</b>	510.1 proc 1	510.2 proc 1	510.3 proc 1	510.4 proc 1	510.5 proc 1
<b>Blowing Sand</b>	-	510.2 proc 2	510.3 proc 2	510.4 proc 2	510.5 proc 2
<b>Vibration</b>	514.2 proc 8/F, W	514.3 proc 1/Cat 10 proc 2/Cat 3	514.4 proc 1/Cat 10 proc 2/Cat 3	514.5 proc 1/Cat 24	514.6 proc 1/Cat 24
<b>Shock</b>	516.2 proc 1/2/3/5	516.3 proc 1/4/6	516.4 proc 1/4/6	516.5 proc 1/4/6	516.6 proc 1/4/6